# TEMPUS CSV-LED

LED Emergency Kit

LED EMERGENCY DRIVER

mackwell®

Model: TEMPUS CSV-LED
Input Voltage: AC85-265V 50-60Hz
Output Voltage: DC 230V
Power for:5-20W LED Lamps
Battery : 11.1V 2600mAH
Battery Duration: 60-180 mins

CE RoHS

Warning: This driver cannot be used for the LED lights with RC driver.

Live
Neutral
Switch
Led lighting
S/N:060720190001

Test
Charge
Emergency
Power

1 or 3 Hours **SELV**

Driver Specification

Model :	TEMPUS CSV- LED
Input Voltage :	AC85-265V 50-60Hz
Output Voltage :	DC 230V
Power for:	5-20W LED Lamps
Battery :	11.1V 2600 mAH
Battery Duration:	60 -180 min s

*Technology features

Mackwell emergency products designed for use with batteries incorporate SmartCharge™ technology consisting of an intermittent charge duty cycle when in charge maintenance mode. This provides energy efficient charging, educed operating temperatures and optimum service life of the battery.

LED emergency Kit

The TEMPUS CSV-LED r ange of LED emergency modules has been designed to enable conversion of general lighting for emergency operations Suitable for operation with DC powered driver and T8-T5 LED tubes

LED Emergency Driver could provide backup emergency power for LED lights to illuminate the pathway when the power outage. Adopts special design to connect various power LED light , whether high power or low power. LED Emergency Kit let your LED light , not only have lighting function , but also can provide emergency light. Wide application , easy installation . All of LED Emergency Module own CE and RoHS certification that you can trust. LED Emergency Battery Backup do not affect the surrounding environment

Dimensions

(27 mm)

(245 mm)

(40 mm)

(245 mm)
Mounting Center

mackwell®
LIGHT THE WAY

CE ICEL